

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Adhesive for plastic patterns

Further trade names

Article No.: 125-140-00

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Health services.

1.3. Details of the supplier of the safety data sheet

Company name: DENTAURUM GmbH & Co. KG

Street: Turnstr. 31

Place: D-75228 Ispringen

Telephone: +49 7231 803 0

Telefax: +49 7231 803 295

e-mail: info@dentaurum.de

Internet: www.dentaurum.com

Further Information

Emergency telephone:

07:00 - 16:15 (Mo - Do), 07:00 - 13:15 (Fr) +49 7231 803 184

16:15 - 18:00 (Mo - Do), 13:15 - 18:00 (Fr) +49 7231 803 0

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

butanone; ethyl methyl ketone

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 2 of 9

P240	Ground and bond container and receiving equipment.
P243	Take action to prevent static discharges.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Contains: resin, Copolymer

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
78-93-3	butanone; ethyl methyl ketone			70-90 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache. Nausea. drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Hazards identification: pneumonia.

after ingestion: Have victim drink large quantities of water, with active charcoal if possible.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder. Water fog.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 3 of 9

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protective suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion
Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Ensure adequate ventilation of the storage area.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against direct sunlight. Keep away from heat.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Health services.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 4 of 9

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes and skin.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not smoke.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Recommendation: Camapren 720

Suitable material: Chloropren

Thickness of glove material: 0,65 mm

penetration time: 10 min

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	like: Acetone

Test method

pH-Value:	not determined
-----------	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 5 of 9

Changes in the physical state

Melting point:	-20 °C
Initial boiling point and boiling range:	85 °C DIN 51751
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	< 10 °C DIN 51755
Sustaining combustion:	No data available

Flammability

Solid:	not applicable
Gas:	not applicable
Lower explosion limits:	1 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	< 300 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined

Oxidizing properties

Not oxidising.	
Vapour pressure: (at 20 °C)	85 hPa
Vapour pressure: (at 60 °C)	280 hPa
Density (at 15 °C):	0,7 g/cm ³ DIN 51757
Bulk density:	not determined
Water solubility: (at 20 °C)	practically insoluble

Solubility in other solvents

not determined	
Partition coefficient:	Distribution coefficient (n-octanol / water) (log P O/W): 3,4 - 4,6
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 20 °C)	0,71 mm ² /s DIN 51562
Flow time:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	not determined
Odour threshold:	not determined

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 6 of 9

10.1. Reactivity

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixtures with air.

Reacts with : Oxidizing agents, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

none

Further information

Thermal decomposition: At normal pressure may be distilled without decomposition.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix tested

	Dose	Species	Source
LD50, oral	2740 mg/kg	Rat	
LD50, dermal	6480 mg/kg	Rabbit	

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

The product is skin resorptive.

Irritant effect on the eye: strongly irritant.

Following inhalation: Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc., Cough, Dyspnoea

Sensitising effects

not sensitising.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

no classification

Aspiration hazard

no classification

Specific effects in experiment on an animal

Causes mild skin irritation. Rabbit.

Causes serious eye irritation. Rabbit.

Practical experience

Other observations

after ingestion: Vomiting, Nausea

The product is skin resorptive. Dizziness, Blood pressure drop, Anaesthetic state

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 7 of 9

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Physicochemical elimination: Product is easily volatile. Is well eliminable from water. (Stripping.)

SECTION 13: Disposal considerations

13.1. Waste treatment methods**Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

In dry state: May be disposed of in household waste landfill.

in delivery condition: This material and its container must be disposed of as hazardous waste.

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)**14.1. UN number:**

UN 1133

14.2. UN proper shipping name:

Adhesives

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

640D

Limited quantity:

5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 8 of 9

Excepted quantity: E2
 Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Marine transport (IMDG)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 5 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Adhesive for plastic patterns

Revision date: 10.03.2020

Product code: 125-140

Page 9 of 9

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)